

# Card Laminator LXS II



## Compact design

Our smallest laminator yet. A compact product from our series of laminators for plastic cards.

## Extremely robust metal construction


Developed with high-quality materials for demanding applications in the industrial area - "no plastic".

## Versatile usable

Adjustable parameters for different card materials and foils.

## Single or dual sided lamination


with optional flipper. Automatic detection of alternative patches for front and back.



Optional: LXS II with card feeder



Optional: LXS II with card feeder and flipper for both-sided card lamination



Optional: LXS II as OEM

## Features

- Roll laminator
- Laminates on plastic cards according to ISO 7810 (54 x 85.6 mm)
- Laminates thin film and patch
- Laminates both-sided by automatic detection with different patches for front and back
- Panel, windows-tool and interface for operating and controlling
- Adjustable parameters for different card materials and foils (including temperature and speed)
- Optional: Card feeder for a maximum of 120 cards
- Optional: Flipper for both-sided card lamination

## Technical Data

- Heated laminating roll, temperature controlled by sensor
- Laminating speed: up to 20mm/s
- Card material: PVC, PE, PC
- Size: 245 x 173 x 190mm (HxWxD)
- Weight: 5.8 kg
- Ambient temperature: +10°C to +40°C, non-condensing humidity 20-80%